

## SHIPPING & HANDLING

SHIPPING INFORMATION								
Product	Container	Ship To	Pallets	Modules	410W Bin			
MSE410HT0B	53'	Most States	26	806	330.46 kW			
Double Stack: (Horizontal Orientation): 31 panels per pallet								

SHIPPING INFORMATION								
Product	Container	Pallet	Modules	550W BIN	Total Weight			
MSN10-550HT4T	40'	20	620	341 kW	40,565 lbs			
MSN10-550HT4G	40'	20	720	396 kW	51,588 lbs			
Product	Container	Pallet	Modules	580W BIN	Total Weight			
MSN10-585HN4G	40'	20	720	417.6 kW	40,565 lbs			

PALLET DIMENSIONS & WEIGHT								
	31 Panels/Pallet		36 Panels/Pallet					
	PERC 108HC	PERC Bifacial 144HC	PERC Bifacial 144HC	TOPCon Bifacial 144HC				
Product	МЅЕ410НТОВ	MSN10-550HT4T	MSN10-550HT4G	MSN10-585HN4G				
Weight	1610 lbs	2029.3 lbs	2759.4 lbs	2759.4 lbs				
Height	51 in	50 in	50 in	50 in				
Length	70 in	90.6 in	90.6 in	90.6 in				
Width	47 in	47.2 in	47.2 in	47.2 in				

## STORAGE TRANSPORT INSTRUCTIONS



Use caution when moving modules around warehouse or job site. Do not exceed rated load capacity of forklift. Only transport a double-stacked pallet if it is well aligned. Do not collide with other objects while transporting modules. Only use fork lifts with long forks (at least 72" or 6') to move the pallets.



Fragile! Modules should be handled carefully. Do not place modules roughly on hard surface or on their corners. Do not drag modules over each other when unstacking.



The packagemust always be transported, handled and stored in such a way that the arrows always point upwards.



Do not step or stand on modules. Do not place any objects on modules.



The cardboard sleeve and package materials are recyclable.



Do not use forklift truck on glass side.



Package and modules should be protected from excessive moisture (rain, snow, etc.) and must accordingly be stored under cover. If package and modules cannot be stored in warehouses or sheds, they must be carefully covered with tarpaulins.



Never stack more than 2 pallets high. Double-stacked pallets need to have anti-slip pads between pallets.



Use two people when unpacking modules from pallet. When handling modules always use both hands and safety gloves.